

# e-therm-Series



### ACCESSORY STORAGE

neat storage for high pressure gun and lances

### CONVENIENT INTEGRATED HOSE REEL (VARIANTE)

space-saving storage of the high-pressure hose - with foldable crank

### DIGITAL CONTROL PANEL

digital temperature regulation with 2 different operation modes

### REMOVABLE COVERS

convenient and easy service access



# 642260 e-therm 603 M 36

► **ACCESSORIES** | starting on page 64



### EQUIPMENT

- Quick release plug-in system D12
- Total-stop system with delayed motor cut-off
- Safety shutdown
- Pressure regulation
- Cleaning Agent Intake
- Locking brake
- Direct suction: Suction height 2.5 m
- Water tank: Volume 12 liters

**Technix Rubber & Plastic Ltd**  
**Newberry Enterprise Centre**  
**Mallow**  
**Co. Cork P51 DE98**  
**Ireland**

### EQUIPMENT HOT WATER ELECTRICALLY HEATED

- Digital thermostat
- Flow monitor
- Overheating protection
- Operating hours meter



# 42280

### VARIANT - NON-MARKING

<b>NOM conversion kit</b> Version without drum	Ord.no.	<b>42280</b>
<b>NOM conversion kit</b> Version with drum	Ord.no.	<b>42281</b>

For further information on NON-Marking please refer to page 74

MODEL	e-therm 500 M 18	e-therm 500 M 24	e-therm 603 M 36	e-therm 873 M 48
<b>Ord.no.</b> without hose drum	<b>642050</b>	<b>642150</b>	<b>642250</b>	<b>642350</b>
<b>Ord.no.</b> incl. hose drum	<b>642060</b>	<b>642160</b>	<b>642260</b>	<b>642360</b>

### TECHNICAL SPECIFICATIONS

Operating pressure	bar   MPa	30-130   3-13	30-130   3-13	30-150   3-15	30-150   3-15
Water output	l/min   l/h	8   480	8   480	10   600	13   780
Admissible overpressure	bar   MPa	150   15	150   15	170   17	170   17
Motor speed	Rpm	1400	1400	1400	1400
Connection	V   ~   Hz   A	400   3   50   29	400   3   50   39	400   3   50   55	400   3   50   76
Power intake	kW	20	27	38	50
Power supply cable	m	5	5	5	5
Plug		CEE 32 A	CEE 63 A	CEE 63 A	CEE 125 A
Dimensions L x W x H without hose drum	mm	1050   800   1015	1050   800   1015	1050   800   1015	1050   800   1015
Dimensions L x W x H incl. hose drum	mm	1050   800   1450	1050   800   1450	1050   800   1450	1050   800   1450
Weight without   incl. hose drum	kg	128   135	128   135	160   167	160   167

### TECHNICAL DATA HOT WATER

Heating of inlet water	°C	32	34	50	46
Heating output	kW	18	24	36	48

### EQUIPMENT

High-pressure hose without hose drum	m   Ord.no.	10 (DN8)   41081	10 (DN8)   41081	10 (DN8)   41081	10 (DN8)   41081
High-pressure hose incl. hose drum	m   Ord.no.	20 (DN8)   443812	20 (DN8)   443812	20 (DN8)   443812	20 (DN8)   443812
Trigger gun with safety catch	Model   Ord.no.	Starlet   123272	Starlet   123272	Starlet   123272	Starlet   123272
Stainless steel lance with flat-jet nozzle	Nozzle   Ord.no.	○ 03   12420-D2503	○ 03   12420-D2503	● 035   12420-D25035	● 05   12420-D2505
Water inlet filter	Ord.no.	13310	13310	13310	13310