

HD-Series



STAINLESS STEEL PRESSURE GAUGE
easy reading of the working pressure

STAINLESS STEEL CARRY HANDLE
portable and space-saving compact design

DETERGENT SUCTION INTAKE
direct dispensing of cleaning agent -
without additional accessories

TOTAL-STOP SYSTEM
automatic standby of the motor reduces noise
and power consumption when not in use

600180 HD 12/130 TS

► **ACCESSORIES** | starting on page 22



EQUIPMENT

- Quick release plug-in system D12
- Total-Stop system
- Pressure regulation
- Cleaning Agent Intake
- Direct suction: Suction height HD 9/80 TS: 1.5 m
- Direct suction: Suction height HD 12/130 TS: 2.5 m

Technix Rubber & Plastic Ltd
Newberry Enterprise Centre
Mallow
Co. Cork P51 DE98
Ireland
P: +353 (0)22-42826

www.technix.ie



MODEL	HD 9/80 TS	HD 12/130 TS
Ord.no.	600130	600180

TECHNICAL SPECIFICATIONS

Operating pressure	bar MPa	30-80 3-8	30-130 3-13
Water output	l/min l/h	9 540	11 660
Admissible overpressure	bar MPa	90 9	145 14.5
Motor speed	Rpm	1400	1400
Connection	V ~ Hz A	230 1 50 7.5	230 1 50 13.5
Power intake Power output	kW	1.6 1.0	2.9 2.2
Power supply cable	m	5	5
Dimensions L x W x H	mm	470 230 320	500 240 320
Weight	kg	24	31

EQUIPMENT

High-pressure hose	m Ord.no.	10 (DN6) 43416	10 (DN6) 43416
Trigger gun with safety catch	Model Ord.no.	M2000 12481	M2000 12481
Lance with regulating nozzle	Nozzle Ord.no.	● 042 12436-M20042	● 042 12436-M20042
Lance with Dirtkiller	Nozzle Ord.no.	● 042 12438-042	● 042 12438-042

