

K 1152-Series



CONVENIENT INTEGRATED HOSE REEL (TST)
space-saving storage of the high-pressure hose-with foldable crank

ONE-PIECE ROTO-MOULD CHASSIS
practically indestructible plastic housing

STAINLESS STEEL PRESSURE GAUGE
easy reading of the working pressure

ACCESSORY STORAGE
neat storage for high pressure gun and lances

OFF-ROAD CAPABILITY AND STABILITY
robust chassis for easy transport and high stability

602020 K 1152 TST

► **ACCESSORIES** | starting on page 22

EQUIPMENT

- Quick release plug-in system D12
- Total-Stop system
- Pressure regulation
- Cleaning Agent Intake

Technix Rubber & Plastic Ltd
Newberry Enterprise Centre
Mallow
Co. Cork P51 DE98
Ireland
P: +353 (0)22-42826
www.technix.ie



MODEL	K 1152 TS K 1152 TST
Ord.no. TS without hose drum	602010
Ord.no. TST incl. hose drum	602020

TECHNICAL SPECIFICATIONS

Operating pressure	bar MPa	30-130 3-13
Water output	l/min l/h	10 600
Admissible overpressure	bar MPa	150 15
Motor speed	Rpm	2800
Connection	V ~ Hz A	230 1 50 12
Power intake Power output	kW	2.8 2.0
Power supply cable	m	5
Dimensions L x W x H	mm	360 365 870
Weight without incl. hose drum	kg	28 30

EQUIPMENT

High-pressure hose TS without hose drum	m Ord.no.	10 (DN 6) 43416
High-pressure hose TST incl. hose drum	m Ord.no.	15 (DN 6) 48015
Trigger gun with safety catch	Model Ord.no.	M2000 12481
Lance with Vario-Jet	Nozzle Ord.no.	● 042 12437-042
Lance with Dirtkiller	Nozzle Ord.no.	● 042 12438-042

