

Alfaflat M

-10°C

+60°C



Very light and easy to manage lay-flat water hose. It is suitable for the transfer of water with no pressure or under very low pressure. Ideal for use on the discharge side of a pump on construction sites (open end), but can also serve as a protective sleeve around cables, hydraulic hoses, lashings, etc.

Construction: Plasticised PVC extruded around a polyester reinforcement, resistant to atmospheric influences.

Colour: Blue

Art. No.	Internal Ø (mm)	Flat Width (mm)	Weight (g/m)	Roll Lengths (m)
MM020	20	31	150	25-50
MM025	25	39	170	25-50-100
MM030	30	47	200	25-50
MM032	32	50	220	25-50-100
MM035	35	55	240	25-50
MM038	38	60	300	25-50-100
MM040	40	63	320	25-50-100
MM045	45	71	350	25-50
MM050	50	78	390	25-50-100
MM055	55	86	510	25-50
MM063	63	99	550	25-50
MM070	70	110	560	25-50-100
MM075	75	118	600	25-50
MM080	80	126	650	25-50
MM090	90	141	730	25-50-100
MM100	100	157	900	25-50
MM110	110	173	1,000	25-50
MM125	125	196	1,100	25-50
MM150	150	236	1,480	25-50
MM200	200	314	2,400	25-50
MM250	250	392	3,000	30-100