

Fuelflex 10 bar



Very flexible PVC hose, especially for hydrocarbons and derivatives
Reinforced by durable textile thread

Temperature: -15°C to +60°C

The Fuelflex is a reinforced pvc hose for conveying hydrocarbons and derivatives up to 10 bar.

Tube: transparent pvc, resistant to hydrocarbons (> Ø20mm black)

Reinforcement: high tensile thread

Cover: transparent blue pvc, resistant to hydrocarbons (> Ø20mm black)

ATTENTION: not for gasoline

Applications

pumps, heaters, ...

Reference	Diameter (mm)	Bending radius (mm)	Weight (g/m)	Working Pressure (bar)	Burst Pressure (bar)	Coil length (m)
TFU06	6,3 x 11	80	50	10	40	50
TFU08	8 x 14	128	60	10	40	25 - 50
TFU10	10 x 16	149	80	10	33	50
TFU12	12 x 19	210	100	10	33	50
TFU15	15 x 23	295	125	10	33	50
TFU20	20 x 28	370	150	10	30	25 - 50
TFU25	25 x 32,5	425	170	8	24	25 - 50
TFU30	30 x 39	598	200	8	24	25 - 50

Technix Rubber & Plastic Ltd

Email: sales@technix.ie

Phone: 022-42826

www.technix.ie