

## Cristal



The Cristal is a very simple hose with food quality. However without reinforcement and as such only to be used at very low pressure, she has wide range of applications

Temperature: -15°C to +60°C

**Construction:** transparant pvc with food quality

PVC hose Food-grade quality without phthalates according to simulants A, B, C, and D1 (approved by the IANESCO testing laboratory E19-10407)

### Applications

Food products, medical labs, various industrial applications

Can also be used as protection hose

### Assembly

nylon-couplings (N66)

Reference	Diameter (mm)	Weight (g/m)	Coil length (m)
CR0204	2 x 4	12	100
CR0305	3 x 5	16	100
CR0306	3 x 6	26	100
CR0406	4 x 6	20	100
CR0407	4 x 7	32	50 - 100
CR0408	4 x 8	47	50 - 100
CR0507	5 x 7	24	50 - 100
CR0508	5 x 8	39	50 - 100
CR0608	6 x 8	28	50 - 100
CR0609	6 x 9	44	50 - 100
CR0610	6 x 10	64	50 - 100
CR0612	6 x 12	108	50 - 100
CR0710	7 x 10	50	50 - 100
CR0810	8 x 10	35	50 - 100
CR0811	8 x 11	56	25 - 50 - 100
CR0812	8 x 12	79	25 - 50 - 100
CR0814	8 x 14	132	50
CR0912	9 x 12	61	50
CR0913	9 x 13	88	50
CR1013	10 x 13	68	50
CR1014	10 x 14	94	25 - 50 - 100
CR1016	10 x 16	112	50
CR1216	12 x 16	110	25 - 50 - 100
CR1217	12 x 17	145	50
CR1319	13 x 19	192	50
CR1418	14 x 18	126	50
CR1419	14 x 19	165	50



CR1519	15 x 19	134	50
CR1520	15 x 20	171	50
CR1521	15 x 21	216	50
CR1620	16 x 20	141	50
CR1621	16 x 21	185	50
CR1622	16 x 22	224	50
CR1822	18 x 22	158	50
CR1823	18 x 23	205	25 - 50
CR1824	18 x 24	252	50
CR1924	19 x 24	211	50
CR1926	19 x 26	309	50
CR2024	20 x 24	173	50
CR2025	20 x 25	225	25 - 50
CR2026	20 x 26	270	50
CR2228	22 x 28	275	50
CR2430	24 x 30	317	25 - 50
CR2531	25 x 31	330	25 - 50
CR2532	25 x 32	400	25 - 50
CR2533	25 x 33	455	25 - 50
CR2535	25 x 35	600	25 - 50
CR2733	27 x 33	354	25 - 50
CR2836	28 x 36	500	25
CR3037	30 x 37	460	25 - 50
CR3038	30 x 38	534	25 - 50
CR3040	30 x 34	688	25
CR3240	32 x 40	565	25 - 50
CR3242	32 x 42	726	25 - 50
CR3542	35 x 42	529	25 - 50
CR3545	35 x 45	800	25
CR3848	38 x 48	844	25 - 50
CR4048	40 x 48	691	25 - 50
CR4049	40 x 49	801	25 - 50
CR4050	40 x 50	900	25 - 50
CR4555	45 x 55	1000	25
CR5060	50 x 60	1080	25 - 50
CR6070	60 x 70	1276	25